



Type of fluid  
**OIL AND  
SIMILAR**

Pressure  
**50-100  
150 bar**

Material  
**- PAINTED STEEL  
- ABS**


WITH SPRING



**FIXED\***



**SWIVELLING**



- with hose, see page 139  
- without hose, max. 80 °C



In accordance with directive



for ABS versions

\* can be rendered swivelling by using the special bracket, see page 81.

#### DRUM COLOURS

Painted   
ABS

| Hoses        | Connections      | Seals        | Swivel joint     | Central pin      |
|--------------|------------------|--------------|------------------|------------------|
| black rubber | galvanized steel | polyurethane | galvanized steel | galvanized steel |
|              |                  |              |                  |                  |

| Overall dimensions FIXED (mm) |  |  |  | Series  | A   | B   | C   | D   | E   | F   | G   | H   | I   | Packaging (mm) W x D x H |                 |
|-------------------------------|--|--|--|---------|-----|-----|-----|-----|-----|-----|-----|-----|-----|--------------------------|-----------------|
|                               |  |  |  | 330     | 186 | 140 | 196 | 226 | 98  | 390 | 350 | 365 | 155 |                          | 510 x 260 x 520 |
|                               |  |  |  | 390     | 186 | 140 | 196 | 226 | 98  | 410 | 390 | 410 | 155 |                          | 580 x 280 x 590 |
|                               |  |  |  | 430     | 186 | 140 | 197 | 226 | 97  | 450 | 415 | 456 | 264 |                          | 580 x 280 x 590 |
|                               |  |  |  | 430 ABS | 186 | 140 | 197 | 226 | 110 | 450 | 425 | 461 | 259 |                          | 580 x 280 x 590 |
|                               |  |  |  | 530     | 203 | 153 | 221 | 258 | 104 | 535 | 510 | 558 | 315 |                          | 650 x 290 x 700 |
|                               |  |  |  | 540     | 300 | 218 | 227 | 268 | 165 | 535 | 510 | 572 | 315 |                          | 660 x 390 x 690 |
|                               |  |  |  | 560     | 488 | 399 | 238 | 272 | 348 | 535 | 510 | 578 | 315 |                          | 670 x 610 x 760 |
|                               |  |  |  |         |     |     |     |     |     |     |     |     |     |                          |                 |



|                              |             | P/N                         |                        | Hose supplied | Connection      |                        | Weight       |            |
|------------------------------|-------------|-----------------------------|------------------------|---------------|-----------------|------------------------|--------------|------------|
|                              |             | fixed                       | swivelling             |               | inlet           | outlet                 | fixed        | swivelling |
|                              |             |                             |                        |               |                 |                        |              |            |
| s. 330<br>150 bar            | 8330.400    | -                           | without hose *         |               | G 1/2" (f)      | G 3/8"(f)<br>G 1/2"(f) | 11,2 kg      | -          |
|                              | 8330.402    | -                           | 12 m - 3/8" (995.312)  |               | G 1/2" (f)      | G 1/2" (m)             | 15,0 kg      | -          |
| * Hose reel capacity         |             | inner hose ø<br>max. length | 1/4"<br>12 m           | 5/16"<br>12 m | 3/8"<br>12 m    | 1/2"<br>8 m            |              |            |
| s. 390<br>150 bar            | 8390.400    | 8380.400                    | without hose *         |               | G 1/2" (f)      | G 3/8"(f)<br>G 1/2"(f) | 13,0 kg      | 13,5 kg    |
|                              | 8390.401    | 8380.401                    | 12 m - 3/8" (995.312)  |               | G 1/2" (f)      | G 1/2" (m)             | 16,8 kg      | 17,3 kg    |
|                              | 8390.402    | 8380.402                    | 17 m - 3/8" (995.317)  |               | G 1/2" (f)      | G 1/2" (m)             | 18,3 kg      | 18,8 kg    |
| * Hose reel capacity         |             | inner hose ø<br>max. length | 1/4"<br>15 m           | 5/16"<br>16 m | 3/8"<br>17 m    | 1/2"<br>12 m           |              |            |
| s. 430<br>150 bar            | 8430.400    | 8420.400                    | without hose *         |               | G 1/2" (f)      | G 1/2" (f)             | 16,0 kg      | 16,5 kg    |
|                              | 8430.401    | 8420.401                    | 10 m - 1/2" (996.310)  |               | G 1/2" (f)      | G 1/2" (m)             | 20,5 kg      | 21,0 kg    |
|                              | 8430.402    | 8420.402                    | 15 m - 1/2" (996.315)  |               | G 1/2" (f)      | G 1/2" (m)             | 12,5 kg      | 13,0 kg    |
|                              | 8430.450    | -                           | without hose **        |               | G 1" (f)        | G 3/4" (f)             | 16,8 kg      | -          |
| s. 430<br>for suction        | 8430.400/AS | -                           | without hose *         |               | G 1/2" (f)      | G 1/2" (f)             | 16,0 kg      | -          |
|                              | 8430.401/AS | 8420.401/AS                 | 10 m - 1/2" (996.310)  |               | G 1/2" (f)      | G 1/2" (m)             | 20,5 kg      | 21,0 kg    |
|                              | 8430.415/AS | -                           | without hose **        |               | G 1/2" (f)      | G 1/2" (m)             | 16,0 kg      | -          |
|                              | 8430.452/AS | -                           | 8 m - 3/4" (997.3308)  |               | G 1" (f)        | G 3/4" (m)             | 22,0 kg      | -          |
| s. 430<br>100 bar            | 8430.415    | -                           | without hose **        |               | G 1/2" (f)      | G 1/2" (m)             | 16,0 kg      | -          |
|                              | 8430.416    | -                           | 10 m - 5/8" (999.3310) |               | G 3/4" (f)      | G 3/4" (m)             | 21,5 kg      | -          |
|                              | 8430.417    | -                           | 8 m - 3/4" (997.3308)  |               | G 3/4" (f)      | G 3/4" (m)             | 22,0 kg      | -          |
| s. 430<br>ABS<br>150 bar     | 9430.400    | -                           | without hose *         |               | G 1/2" (f)      | G 1/2" (f)             | 12,5 kg      | -          |
|                              | 9430.401    | -                           | 10 m - 1/2" (996.310)  |               | G 1/2" (f)      | G 1/2" (m)             | 17,0 kg      | -          |
|                              | 9430.402    | -                           | 15 m - 1/2" (996.315)  |               | G 1/2" (f)      | G 1/2" (m)             | 19,0 kg      | -          |
| s. 430<br>ABS for<br>suction | 9430.400/AS | -                           | without hose *         |               | G 1/2" (f)      | G 1/2" (f)             | 12,5 kg      | -          |
| s. 430<br>ABS<br>100 bar     | 9430.415    | -                           | without hose **        |               | G 1/2" (f)      | G 1/2" (m)             | 12,5 kg      | -          |
|                              | 9430.416    | -                           | 10 m - 5/8" (999.3310) |               | G 3/4" (f)      | G 3/4" (m)             | 17,0 kg      | -          |
|                              | 9430.417    | -                           | 8 m - 3/4" (997.3308)  |               | G 3/4" (f)      | G 3/4" (m)             | 17,5 kg      | -          |
| Hose reel capacity           |             | inner hose ø<br>max. length | * 5/16"<br>20 m        | 3/8"<br>20 m  | 1/2"<br>16 m    | ** 5/8"<br>14 m        | 3/4"<br>8 m  |            |
| s. 530<br>150 bar            | 8530.400    | 8520.400                    | without hose *         |               | G 1/2" (f)      | G 1/2" (f)             | 21,0 kg      | 22,0 kg    |
|                              | 8530.401    | 8520.401                    | 20 m - 1/2" (996.320)  |               | G 1/2" (f)      | G 1/2" (m)             | 29,2 kg      | 30,2 kg    |
|                              | 8530.402    | 8520.402                    | 25 m - 1/2" (996.325)  |               | G 1/2" (f)      | G 1/2" (m)             | 31,1 kg      | 32,1 kg    |
| s. 530<br>100 bar            | 8530.415    | -                           | without hose **        |               | G 1" (f)        | G 1" (f)               | 21,0 kg      | -          |
|                              | 8530.416    | -                           | 12 m - 3/4" (997.3312) |               | G 1" (f)        | G 3/4" (m)             | 28,8 kg      | -          |
| Hose reel capacity           |             | inner hose ø<br>max. length | * 3/8"<br>25 m         | 1/2"<br>25 m  | 5/8"<br>22 m    | ** 3/4"<br>12 m        | 1"<br>8 m    |            |
| s. 540<br>150 bar            | 8540.400    | 8550.400                    | without hose *         |               | G 1" (f)        | G 1" (f)               | 28,0 kg      | 33,5 kg    |
|                              | 8540.405    | 8550.405                    | without hose **        |               | G 1/2" (f)      | G 1/2" (f)             | 28,0 kg      | 33,5 kg    |
|                              | 8540.406    | 8550.406                    | 30 m - 1/2" (996.330)  |               | G 1/2" (f)      | G 1/2" (m)             | 40,3 kg      | 45,8 kg    |
| s. 540<br>100 bar            | 8540.411    | 8550.411                    | 15 m - 3/4" (997.3315) |               | G 1" (f)        | G 3/4" (m)             | 37,6 kg      | 43,1 kg    |
|                              | 8540.412    | 8550.412                    | 20 m - 3/4" (997.3320) |               | G 1" (f)        | G 3/4" (m)             | 40,2 kg      | 45,7 kg    |
| s. 540<br>50 bar             | 8540.413    | 8550.413                    | 15 m - 1" (998.3315)   |               | G 1" (f)        | G 1" (m)               | 42,6 kg      | 48,1 kg    |
|                              | 8540.414    | -                           | 10 m - 1" (998.3310)   |               | G 1" (f)        | G 1" (m)               | 38,2 kg      | -          |
| Hose reel capacity           |             | inner hose ø<br>max. length | * 3/4"<br>22 m         | 1"<br>15 m    | ** 3/8"<br>30 m | 1/2"<br>30 m           | 5/8"<br>30 m |            |
| s. 560<br>150 bar            | 8560.400    | -                           | without hose *         |               | G 1" (f)        | G 1" (f)               | 48,0 kg      | -          |
| * Hose reel capacity         |             | inner hose ø<br>max. length | 5/8"<br>50 m           | 3/4"<br>40 m  | 1"<br>30 m      |                        |              |            |

Prepared with outlet connection for ø 3/4" hoses